

Standard Features For All Cals

Hull, Deck, and Rigging

- One piece hand laminated fiberglass hulls and decks.
- Molded-in hull, stripe, and two-tone deck colors.
- Foam and plywood cored decks with molded non-skid pattern.
- Bronze below water thru-hulls with seacocks.
- Stainless steel chainplates bolted to bulkhead or knees bonded to hull.
- Flush anchor locker in foredeck with overboard drain.
- Stainless steel double rail bow and stern pulpits with transom gate; stainless steel stanchions.
- Barient winches.
- Mainshet travelers.
- Painted aluminum masts and booms.
- Double internal reef, internal outhaul, external adjustable boom topping lift.
- Standing rigging is 1 x 19 stainless steel cable with swaged terminals; stainless steel and chromed bronze turnbuckles, flush tangs and T-terminals on shrouds.
- Internal main and jib halyards; yacht braid tails spliced to stainless steel halyard cable.
- Yacht braid running rigging.
- Boom vang package.
- Bow light and anchor light.
- Deck hardware is chrome plated bronze, stainless steel or anodized aluminum (silver color deck hardware).
- Fiberglass covered high density foam rudder with stainless steel rudder shaft.
- Seahoods and solid teak penboards.

Interior

- Fiberglass floor pan extends throughout interior, bonded to hull for added strength.
 - Teak bulkheads, cabinets and trim throughout interior, except head.
 - Heads finished in white laminate with teak trim.
 - Foam backed fabric or vinyl hull liner for sound and moisture insulation. Fabric is treated to resist stains.
 - Towel ring, glass and toothbrush holder, toilet paper holder, and mirrors in head.
 - Stainless steel sinks in galley and head.
- ### Machinery, Electrical and Plumbing
- 12 volt circuit breaker panels with battery volt meter, and power-on light and battery selector switch.
 - FDA approved plumbing.
 - Lightning ground system.
 - Manual bilge pump accessible with all hatches closed.
 - Sound insulation in engine room.

Cal 39 Mark III Standard Features.

Hull and Deck

- Internal lead ballast bonded in place.
- Flat area on centerline forward for mounting instrument transducers.
- Cast aluminum stemhead fitting with double anchor rollers.
- Custom extruded anodized aluminum toe rail.
- Double lifelines with a boarding gate to starboard. Stern pulpit has integral, fold-down swim ladder.
- 24" x 24" Aluminum framed translucent hatch mounted on foredeck.

- 20" x 20" Aluminum framed translucent hatch mounted over main cabin.
 - Sea hood for companionway hatch, with integral traveler mount and dorade boxes.
 - Teak hand rails on cabin top.
 - Teak eyebrow on cabin house.
 - 2 - 12" x 1 1/2" Aluminum sheet tracks mounted inboard on the deck; sheet blocks on each track.
 - Lockable seat hatch opens to a molded storage bin.
 - Lazarett hatch aft opens to a molded bin.
 - Starboard seat hatch.
 - 2 #28 Barient chrome genoa sheet winches with cleats.
 - Pedestal steering with 32" wheel; pedestal guard, brake and controls mounted on pedestal; emergency tiller provided.
 - Engine instruments mounted in cockpit include: tachometer, oil pressure, water temperature, and amp meter.
 - Mainshet traveler mounted on cabin top; controls lead to cockpit.
 - 1 #18 Barient chrome mainsheet winch.
- ### Spars and Rigging
- Single spreaders, double lower shrouds, masthead sloop rig.
 - 1 #18 Barient chrome main halyard winch.
 - 1 #22 Barient chrome genoa halyard winch.
 - 2:1 Boom topping lift with adjustment on boom.
 - 4:1 Internal outhaul.
 - 5:1 Mainsheet purchase; 1 #18 Barient chrome mainsheet winch with cleat, mounted on cabin top to port of companionway.
- ### Interior Structure
- Removable vinyl headliner in main cabin, galley and aft stateroom.
 - Varminished teak and holly cabin sole, except in head area.
- ### Forward Stateroom
- 4" Fabric covered foam cushions.
 - Cedar lined hanging locker with shelf over, and louvered teak door.
- ### Head
- Marine head discharges to holding tank with deck discharge.
 - Vanity with stainless steel sink, pressure hot and cold water, shower, storage under; medicine cabinet/linen locker over; mirrored plexiglass doors.
 - Teak framed oval mirror on bulkhead.
 - Teak louvered door.

Main Cabin

- Settees with 5" fabric covered foam cushions. Padded seat backs swing up to increase bunk space. Berths measure 6'4" x 3'6".
 - Alcoves and lockers with louvered doors.
 - Centerline drop-leaf table finished in teak and white laminate; fiddles on leaves; bin on table top; table hangs on mast and stainless steel clutch post.
 - Leaded glass liquor locker and bureau forward of starboard settee.
 - Chart table aft of port settee with hinged top opening to chart storage; shelves for electronics, etc., storage cabinets under; gooseneck navigation lamp with red bulb.
 - Lights on forward bulkheads, chart table bulkheads and over table.
 - 6'3" Headroom.
 - Vinyl boot covers mast.
- ### Galley
- 8.0 cubic foot ice box with tray; polyurethane foamed-on insulation.

- Double stainless steel sinks with pressure hot and cold water.
 - 3-Burner alcohol stove with oven.
 - Dorade ventilator over galley.
 - Teak companionway ladder mounted on removable panel for engine access.
- ### Aft Cabin
- Hanging locker with louvered teak door; vanity with sink, pressure hot and cold water, and storage.
 - Double berth with 5" fabric covered foam mattress. Berth measures 6'5" x 4'2".
 - Drawer and large storage bins under berth.
 - Dorade ventilator over forward end of cabin.
 - 6'3" Headroom.
- ### Mechanical and Plumbing
- Pathfinder 40HP 4-cylinder fresh water cooled diesel engine with 1 1/4" bronze shaft and 2-blade propeller.
 - 45 Gallon aluminum fuel tank.
 - 2 - 105 amp/hour marine batteries in plastic boxes.
 - Master electrical control panel, 12 Volt system includes: battery selector/disconnect switch, circuit breakers and battery condition volt meter, 110V system includes: master circuit breaker, branch line circuit breakers and reverse polarity indicator and 50" power cord.
 - International running lights mounted on pulpits.
 - Lightning ground.
 - 130 Gallons of fresh water in 2 stainless steel tanks with deck fills; level gauges for each tank.
 - 6 Gallon hot water heater operates off 110V AC system and heat exchanger.
 - Electric, self-priming water pressure pump, with water tank selector valve.
 - Gusher 10 manual bilge pump, accessible with all hatches closed.
 - Electric bilge pump.

Cal 39 Options.

- *Compass - Pedestal Mount* - Ritchie SP-5 or equivalent installed in steering pedestal.
- *Cradle* - Shipping/storage cradle specifically designed for the Cal 39.
- *Overboard Discharge Head* - Addition to standard head installation that allows overboard discharge of head in uncontrolled waters.
- *Raw Water Strainer for Engine* - Raw water strainer placed between thru-hull and engine will protect cooling system of engine from foreign particles that may be sucked in by water pump.
- *Salt Water Galley Pump* - Self-priming manual pump, mounted at the galley sink. Thru-hull pick-up is equipped with flush bronze fitting and gate valve.
- *Self-tailing Winches* - 2 #28ST Barient chrome winches mounted in lieu of the standard #28 genoa winches, and/or 1 ea. #19ST chrome Barient mounted in lieu of the standard #18 mainsheet winch.
- *Special Hull Colors* - See gelcoat chart for available colors.
- *Tail Rig* - Option increases 1' dimension of rig from 50' to 54'.
- *Three-Burner CNG Stove with Oven* - Gas systems, or equivalent stove unit. CNG stove systems offer the safest method of cooking onboard due to the fact that natural gas rises, rather than sinking to the bilge. Stove unit comes complete with fuel tank, regulator and shutoff valve.
- *Three-Burner Propane Stove with Oven* - High quality, marine propane stove complete with tank, regulator, high pressure hose and safety shutoff valve. Fuel tank is mounted in a separate Fiberglass locker equipped with sealed lid and overboard drain.

Specifications shown in this catalog (standards, options, etc.) are subject to change without notice. Some photos may show optional or special equipment and accessories used as photographic props.

